

LOBO

advanced platform system

Product Application – Portable Lifting Slider Beam



LOBO Systems provides easy to attach lifting slider beams in a range of lengths.

The beams are fitted to standard LOBO components or integrated into a LOBO System with ease.

This is all done without the need for any tools and yet can be flat packed for transport or storage.



Quick to assemble, they can be used for many industrial applications to assist in the maintenance of pumps, gearboxes, motors and many other machines.

LOBO beams can be positioned within a LOBO structure to facilitate limitless applications.



www.lobosystems.com

Conformities

EU: BS EN1004:2004 BS 1139 parts 3 & 4,

USA: Complies to OSHA CFR 29 1926 450-454 & sub part L & codified under 29 CFR 1910.27(a).

Canada: CSA Z797-09 and 269.2 (M87 and -16)

Australia: AS/NZS 1576.1:2010 and AS/NZS 1576.3:2015 Tower





Beams are rated and certified with a Safe Working Load (SWL) of 500Kg/1100 lbs maximum.

LOBO Slider Beams are designed to fully integrate with the LOBO System or can be configured freestanding.



Five lengths are available: 1.2m/4ft | 1.8m/6ft | 2.4m/8ft | 3.0m/10ft | 3.6m/12ft
All rated at 500Kg/1100 lbs.

www.lobosystems.com

Conformities

EU: BS EN1004:2004 BS 1139 parts 3 & 4,
USA: Complies to OSHA CFR 29 1926 450-454 & sub part L & codified under 29 CFR 1910.27(a).
Canada: CSA Z797-09 and 269.2 (M87 and -16)
Australia: AS/NZS 1576.1:2010 and AS/NZS 1576.3:2015 Tower

